

INB716Z-RWTN

2 Megapixel Premium Series IP IR WDR Bullet Camera

Infinique offers a wide range of IP based high definition cameras from 1.4MP to 6MP available in various housing formats, including Box, Dome and Bullet. Our cameras are equipped with superior image sensor and digital signal processor to produce sharp, crisp pictures and are enclosed in weather and vandal resistant housings making it suitable for use in all security applications. The ONVIF compliance of the cameras helps in easy integration, providing peace of mind for your investment. From small to very large installations, Infinique's cameras are reliable, future proof and an ideal solution for your video surveillance needs.

The INB716Z-RWTN is a 2 Megapixel IP IR bullet camera incorporating a 1/2.8" high quality image sensor and has a 130dB wide dynamic range providing sharp images and a wide field of view maintaining high level of image detail even when the video is digitally zoomed. It's powerful array LEDs providing clear crisp images during the night for a distance of up to 80 meters.

The camera comes equipped with a 5~50mm motorized lens with remote zoom and focus for easy setup of field of view. Auto Iris control allows the camera to automatically set its iris position to maximize image quality in all lighting conditions. The camera streams real-time video at high definition resolution using H.265 or H.264 compression optimizing the bandwidth and increasing storage efficiency.


Built-in PoE for powering the camera and the concealed cable bracket for fixing it on ceiling or wall, provides the convenience for installers to complete the installation quickly and with ease. These excellent IP cameras are highly suitable for video surveillance of government buildings, residential apartments, schools, colleges, universities, shopping malls, hospitals, hotels, industrial parks, corporate offices and can also be used for vehicle Number Plate Recognition (NPR) applications.

Product Features

- 1/2.8" Progressive Sensor
- 2 Megapixel Resolution at 30fps
- IR Distance 80 meters
- 5~50mm Motorized Zoom Lens
- 130dB True WDR
- H.265, H.264 Compression
- Up to 3 Simultaneous Video Streams
- S/N Ratio of more than 50dB
- Micro SD Card Slot for Onboard Storage
- Composite Video Output
- Two Way Audio, Alarm I/O
- Power Over Ethernet (PoE), IEEE 802.3af
- IP67 Rated
- Vandal Proof Aluminum Alloy Housing
- Wall or Ceiling Mount with 3 Axis Bracket
- ONVIF Compliant



Dimensions



Accessories







Part Number: IJBBCM-134 Ceiling Mount Junction Box



Part No: IBKTCM Pendant Ceiling Bracket



Part No: IBBCPM Pole Mount Bracket

INB716Z-RWTN





IMAGE PERFORMANC	`E	
Image Sensor	1/2.8" Progressive Sensor	
Effective Pixels (H x V)	1920 × 1080	
Resolution (Megapixels)	2	
Minimum Illumination	0.002 lux (AGC ON) 0 lux with IR ON	
Image Rate (FPS)	30	
S/N Ratio	More than 50dB	
IR Distance (m)	80	
LENS		
Focal Length (mm)	5~50 Motorized Zoom Lens	
Iris	DC Auto Iris, Manual	
Aperture Ratio	F2.0	
Angle of View (deg)	H:54.9 (Wide)~6 (Tele), V:42.6 (Wide)~4.5 (Tele)	
VIDEO AND AUDIO		
Video Compression	H.265 Main Profile H.264 Baseline Profile/Main Profile/High Profile	
Main Stream	1920 x 1080, 1280 x 960, 1280 x 720	
Sub Stream	1280 x 720, 640 x 480, 320 x 240	
Mobile Stream	640 x 480, 320 x 240	
Electronic Shutter Control	1/5 ~ 1/20000	
Day/Night Control	True Day/Night with IR Cut Filter	
Flicker Control	50 Hz, 60 Hz	
True WDR	130dB, On / Off / Adjustable Level	
3D Noise Reduction	Auto / Manual / Disable	
White Balance	Automatic / Manual	
Back Light Compensation	On / Off	
Privacy Mask Zones	Up to 4 Privacy Mask Zones	
Automatic Gain Control	Auto/Manual, Adjustable Level	
Audio Compression	G.711A/G.711U/G.726, ADPCM, AAC	
Audio Input / Output	Line level input and output, 3.5mm A/V Interface	
Video Output	BNC	
RS-485	1 RS485 Interface	
Alarm I/O	1CH Alarm Input, 1CH Alarm Output	
Video Bit rate	32Kbps~8Mbps, Supports CBR/VBR	
OSD	Camera ID, Timestamp, Bit rate	
Image Orientation	Lens Flip, Image Flip, Corridor Mode, Rotation	
Image Controls	Hue, Brightness, Contrast, Saturation, Sharpness	
Advanced Functions	Image Rotation, Gain Control, Anti-Fog, Anti-False Color, Anti-Shake, IR Detection	
VIDEO ANALYTICS	· · · · · · · · · · · · · · · · · · ·	
Motion Detection	Multiple Zones	
Advance Video Analytics	Tamper, Out Of Focus, Sound, Perimeter Intrusion, Line Crossing, Stationary Object, Pedestrian Detection, People Counting, Face Detection	

LOCAL STORAGE	
Storage Type	Micro SD card, Max up to 128GB
Recording	Video and Image; Auto / Schedule/ Manual / On Event
NETWORK	
Network Port	10/100M BASE-TX, RJ-45 Connector
Cabling Type	Category 6 and higher
Network Protocol	IPv4, HTTP, HTTPS, TCP/IP, Unicast/Multicast, UDP, RTP, RTSP, RTCP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, SNMP, UPNP, IEEE802.1X
ONVIF Protocol	ONVIF Compliant
Security	User Access with password protection, IP Filtering
Users	1 Administrator, 6 Users
Simultaneous Viewing	Up to 5 users
PC Web Browser	IE 6.0 Above; Mozilla Firefox; Google Chrome
Mobile Device	Windows Mobile, Symbian, iPhone, Android
Events	Motion, Tamper Detection, Sensor, Network Failure
Event Handlers	FTP, E-mail, Local Storage
MECHANICAL	
Housing ID	V4BOMWH671080A1
Dimensions (mm)	90 (W) x 301.11 (L) x 97 (H)
Weight (g)	1427
Housing	Vandal Resistant Aluminum Alloy Housing
Finish	White Powder Coat, RAL 9003 Black Powder Coat, RAL 9004
Installation	Ceiling Mount / Wall Mount, 3-Axis Concealed Bracket
ELECTRICAL	
Power Consumption	580mA, 12V DC, 7 Watts
Power Source	PoE IEEE802.3af; DC12V; AC 24
Power Connector	DC Male Plug
RTC Backup Battery	3V Magnesium Lithium
ENVIRONMENTAL	
Operating Temperature (C)	-20 to +60
Storage Temperature (C)	-20 to +60
Operating Humidity	0% - 95% non condensing
Ingress Protection Rating	IP67
Impact Rating	IK10
STANDARDS COMPLIA	NCE
Emissions	FCC Part 15 Subpart B Class B EN 55022:2010 IC ICES-003 Class B
Immunity	EN 55024:2010
·	

UL 609501, EU: 2001/95/EC GPSD

ORDERING INFORMATION		
PART NUMBER	DESCRIPTION	
INB716Z-RWTN	Infinique Premium Series IR WDR Bullet Camera, 1/2.8 Sensor, 2MP, 5-50mm Motorized Zoom Lens, IR Array LED, 80m IR Range, H.265, H.264, MJPEG, Three Video Streams, 130dB WDR, True Day and Night with ICR, Adjustable Bit Rate, ONVIF Compliant, PoE, IP67, Color White	
INB716Z-RWTNB	Infinique Premium Series IR WDR Bullet Camera, 1/2.8 Sensor, 2MP, 5-50mm Motorized Zoom Lens, IR Array LED, 80m IR Range, H.265, H.264, MJPEG, Three Video Streams, 130dB WDR, True Day and Night with ICR, Adjustable Bit Rate, ONVIF Compliant, PoE, IP67, Color Black	
IJBBWM-134	Infinique Wall Mount Junction Box, Base Diameter 134.3 mm	
IJBBCM-134	Infinique Ceiling Mount Junction Box, Base Diameter 134.3 mm	
IBKTCM	Infinique Pendant Mount Ceiling Bracket, 45 (D) x 294 (H) mm	
IBBCPM	Infinique Pole Mount Bracket with Metal Ties, 125 (L) x 46 (W) x 200 (H) mm	


Safety



Housing Accessories











Infinique Infinique, a Canadian company is a manufacturer of high performing end-to-end solutions in copper, fiber and video surveillance systems. For more information visit our website at www.infinique.com or email us at sales@infinique.com.