

## INB813Z-RWTS

### 3 Megapixel 130dB WDR Bullet Camera with IR

Infinique offers a wide range of IP based high definition cameras from 1.4MP to 6MP which are available in Box, Dome and Bullet housing. Our cameras are equipped with superior image sensor and digital signal processor to produce sharp, crisp pictures and are enclosed in weather-proof vandal resistant housing making it suitable for use in different types of applications. The ONVIF compliance of our cameras helps in easy integration, providing peace of mind for your investment. From small to very large installations, Infinique's cameras are reliable, future proof and an ideal solution for your video surveillance needs.

The INB813Z-RWTS is a 3 Megapixel IR WDR Bullet Camera with weather-proof vandal resistant aluminum housing, incorporating a 1/3" high quality image sensor and IR LEDs it provides clear crisp images both during the Day and Night.

The camera comes equipped with a 2.8~12mm motorized lens providing remote zoom and focus for easy setup of field of view. The Auto Iris control allows the camera to automatically set its iris position to maximize image quality in all lighting conditions. The camera streams real-time video at high definition resolution using H.264 or H.265 compression optimizing the bandwidth and increasing storage efficiency.


Built-in PoE for powering the camera and the flexible 3-axis bracket for fixing it on ceiling or wall, provides the convenience for installers to complete the installation quickly and with ease. These excellent IP cameras are highly suitable for video surveillance of government buildings, residential apartments, schools, colleges, universities, shopping malls, hospitals, hotels, industrial parks, and corporate offices.

#### Product Features

- 1/3" Progressive Sensor
- 3 Megapixel Resolution at 25/30 fps
- 130dB True WDR
- IR LEDs, IR Distance 35 meters
- 2.8~12mm Motorized Zoom Lens
- S/N Ratio of more than 50dB
- H.264, H.265 Compression
- Up to 3 Simultaneous Video Streams
- Power Over Ethernet (PoE), IEEE 802.3af
- IP66 Rated Weather Proof Housing
- Vandal Proof Aluminum Alloy Housing
- Wall or Ceiling mount with 3 Axis Bracket
- ONVIF Compliant Profile-S



#### Dimensions



# INB813Z-RWTS

3 Megapixel 130dB WDR Bullet Camera with IR



IMAGE PERFORMANCE	
Image Sensor	1/3" Progressive Sensor
Effective Pixels (H x V)	2048 x 1536
Resolution (Megapixels)	3
Minimum Illumination	0 lux with IR on
Image Rate (FPS)	25/30, adjustable for all resolutions
S/N Ratio	More than 50dB
IR Distance (m)	35
LENS	
Focal Length (mm)	2.8--12 Motorized Zoom Lens
Iris	DC Auto Iris, Manual
Aperture Ratio	F1.2
Angle of View (deg)	H:108.6 (Wide)--22.4 (Tele), V:81.4 (Wide)--15.8 (Tele)
VIDEO AND AUDIO	
Video Compression	H.265 Main Profile H.264 Baseline Profile/Main Profile/High Profile
Main Stream	2048x1536, 1920x1080, 1280x960, 1280x720
Sub Stream	1280x720, 640x480, 320x240, (1920x1080 Optional Ver)
Mobile Stream	640 x 480, 320 x 240
Electronic Shutter Control	1/5 ~ 1/20,000 sec
Day/Night Control	True Day/Night with IR Cut Filter
Flicker Control	50 Hz, 60 Hz
True WDR	130dB, On / Off / Adjustable Level
3D Noise Reduction	Auto / Manual / Disable
White Balance	Auto / Manual / Indoor
Backlight Compensation	On / Off
High Light Compensation	On / Off
Automatic Gain Control	Off / Low / Mid / High
Privacy Mask Zones	Up to 4 Privacy Mask Zones
Video Bit rate	256K-8M ,Supports CBR/VBR
OSD	Camera ID, Timestamp
Image Orientation	Lens Flip, Image Flip, Corridor Mode, Rotation
Image Controls	Hue, Brightness, Contrast, Saturation, Sharpness
Advanced Functions	Image Rotation, Gain Control, Anti-Fog, Anti-False Color, Anti-Shake, IR Detection
VIDEO ANALYTICS	
Motion Detection	Multiple Zones
Advance Video Analytics	Tamper, Out Of Focus, Sound, Perimeter Intrusion, Line Crossing, Stationary Object, Pedestrian Detection, People Counting, Face Detection

NETWORK	
Network Port	10/100M BASE-TX, RJ-45 Connector
Cabling Type	Category 6 and higher
Network Protocol	IPv4, HTTP, HTTPS, TCP/IP, Unicast/Multicast, UDP, RTP, RTSP, RTCP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, SNMP, UPNP, IEEE802.1X
ONVIF Protocol	ONVIF Compliant
Security	User Access with password protection, IP Filtering
Users	1 Administrator, 6 Users
Simultaneous Viewing	Up to 5 users
PC Web Browser	IE 6.0 Above; Mozilla Firefox; Google Chrome
Mobile Device	Windows Mobile, Symbian, iPhone, Android
Events	Motion, Tamper Detection, Sensor, Network Failure
Event Handlers	FTP, E-mail, Local Storage
MECHANICAL	
Housing ID	V4BOMWH660830S1
Dimensions (mm)	84 (D) x 239 (L) x 79 (H)
Weight (g)	650
Housing	Vandal Resistant Aluminum Alloy Housing
Finish	White Powder Coat, RAL 9003
Installation	Ceiling Mount / Wall Mount, 3-Axis Concealed Bracket
ELECTRICAL	
Power Consumption	440mA, 12V DC, 5.28 Watts
Power Source	PoE IEEE802.3af; DC12V
Input Voltage	PoE, DC 12V
Power Connector	DC Male Plug
RTC Backup Battery	3V Magnesium Lithium
ENVIRONMENTAL	
Operating Temperature (C)	-20 to +50
Storage Temperature (C)	-20 to +60
Operating Humidity	0% - 95% non condensing
Ingress Protection Rating	IP66
STANDARDS COMPLIANCE	
Emissions	FCC Part 15 Subpart B Class B EN 55022:2010 IC ICES-003 Class B
Immunity	EN 55024:2010
Safety	UL 609501, EU: 2001/95/EC GPSD

ORDERING INFORMATION	
PART NUMBER	DESCRIPTION
INB813Z-RWTS	Infinique Premium Series Outdoor IR Bullet Camera, 1/3 CMOS Sensor, 3MP, 25/30fps, 2.8-12mm Motorized Zoom Lens, IR LED, 35m IR Range, H.265, H.264, Three Video Streams, 130dB WDR, True Day and Night with ICR, Adjustable Bit Rate, ONVIF Compliant, PoE, IP66



Infinique, a Canadian company is a manufacturer of high performing end-to-end solutions in copper, fiber and video surveillance systems. For more information visit our website at [www.infinique.com](http://www.infinique.com) or email us at [sales@infinique.com](mailto:sales@infinique.com).