

## INR128-640F16E-3E1

Premium Series 128 Channels NVR, Rack Mountable 3U Chassis



Infinique offers a wide range of video management solutions for IP based video surveillance that are extremely easy to install, use and maintain. The hardware is optimized for video surveillance by consolidating disparate components into a single chassis which is energy efficient and greatly improves the total cost of ownership. The application software has an open architecture that comply to Onvif and industry standard protocols, making it future proof and providing peace of mind for your investment. From small to very large installations, Infinique's IP based video recorders are an ideal solution for today's high demanding video surveillance needs.

Designed as a plug-and-play NVR, installation and commissioning is effortless. The NVR is ONVIF compliant and supports IP cameras with resolution ranging from 1 to 12 Megapixels. On a single NVR depending on the model recording and playback video streams ranging from 64 and 128 channels are supported. It has support for installing up to 16 SATA HDDs internally and can provide a maximum storage capacity of 192TB when using a 12TB hard drive.

Surveillance Client, is a powerful and user friendly Central Management Software that comes free with the NVR. It allows users to connect to multiple NVRs and cameras at geographically dispersed locations. Users can create groups and assign cameras from different NVRs. They can also create user accounts to cater to different user privileges. The interactive map monitor allows users to have a complete visual overview of installation from a single client using imported maps for easy identification and navigation.

## **Product Features**

- Supports 128 channels with up to 12M resolution
- Embedded Linux OS and VMS with no moving parts for increased system response time and reliability
- Plug-and-play device designed for easy and faster commissioning
- Install up to 16 SATA HDDs, provides a maximum storage capacity of 192TB when using 12TB Hard Drives
- 1x ESATA Port, 2x RJ45 Ethernet 1000 Base-T Ports
- Supports H.265, H.264 and MJPEG Compression
- Record Bandwidth of maximum 1024Mbps
- ONVIF Compliant and supports IP cameras with resolution ranging from 1 to 12 Megapixels
- Continuous, Motion Detection, and Alarm recording supported
- Supports Artificial Intelligence features such as face, vehicle and pedestrian detection when connected to compatible Infinique cameras
- Backup using USB Storage Device, HDD or over a Network
- View live video remotely using Central Monitoring Software on a PC or via an app on iPhone and Android devices.
- Supports ONVIF and RTSP video protocols
- Energy efficient, has a very low power consumption
- Easy to install, comes with standard rack mountable chassis.

## INR128-640F16E-3E1



## Premium Series 128 Channels NVR, Rack Mountable 3U Chassis

SYSTEM	
Operating System	Linux and X-Windows with OpenGL
User Interface	User Friendly Graphical User Interface
Camera Channels	128 Channels
Internal Storage	16x SATA HDD Hot Swappable Bays
RAID	0/1/4/5/6/10
USB Interface	1x 2.0 USB (Front), 2x 3.0 USB (Rear)
Alarm Ports	16x Digital Inputs, 4x Digital Outputs
Ethernet Interface	2x GbE Ports
PoE Ports	No Built in PoE
RS232	1x RJ45
RS485	Yes
Cameras Supported	Infinique, ONVIF Compliant Cameras
CLIENT MODULES	
CMS	Windows / MAC
Mobile App	Android / iOS
Web Browser	IE v9 and above
VIDEO AND AUDIO	
Maximum Resolution	Up to 12MP
Video Outputs	4x HDMI Ports (4K), 1x HDMI Ports Full HD
Video Standards	NTSC 60 Hz, PAL 50 Hz
Video Decoding	H.265, H2.64 and MJPEG
Audio Ports	1 x Audio In, 1 x Audio Out
DISPLAY AND RECORD	DING
Resolution Supported	12MP, 8MP(4K), 5MP, 4MP, 3MP, 2MP(1080P), 1.3MP (960P), 1MP(720P)
Record Bandwidth	1024Mbps
Record Mode	Continuous, Motion Detection, and Alarm Trigger Recording
Live / Playback	12MP @120fps, 8MP @240fps, 4MP @480fps, 2MP @960fps
Display Split	1/4/6/8/9/10/13/14/16/17/19/22/25/32/36
Advance Video Analytics*	Perimeter Intrusion, Line Crossing, Stationary Object, Pedestrian Detection, Face Detection , Heat Map, Sound Detection, People Counting * when recorded with Infinique cameras

MECHANICAL	
Form Factor	Rack Mountable Chassis
Dimensions (mm)	440(W) x 460(D) x 189(H)
Weight (kg)	TBD
ELECTRICAL	
Power Consumption (Excluding HDD)	TBD
Power Supply	AC 110~240V ATX 250W
ENVIRONMENTAL	<u>'</u>
Operating Temperature (C)	10° to 40 (50° to 95°F)
Storage Temperature (C)	-40 to 70 (-40° to 158°F)
Operating Humidity	8% to 90%, non-condensing
Non-Operating Humidity	5% to 95%, non-condensing
Operating Altitude (m)	-16m to 3048m (-50ft to 10,000ft)
significantly higher than the	tion, etc. The NVR air intake temperature, can be room temperature. To prevent system and hard drive intake temperature of the NVR is always within the experience.
ACCESSORIES SUPPLIED	)
Power Cord	Based on country; 3 prong molded connector, 1.8 m (6 ft) Cord Length
USB Mouse	1nos
USB Mouse Documentation	1nos Manual on CD
	Manual on CD
Documentation	Manual on CD
Documentation STANDARDS COMPLIAN	Manual on CD  ICE  FCC Part 15 Subpart B Class A EN55032:2015+A11:2020+A1:2020 EN IEC 61000-3-2:2019+A1:2021 EN 61000-3-3:2013+A1:2019+A2:2021

ORDERING INFORMATION		
PART NUMBER	DESCRIPTION	
	Infinique Premium Series 128Ch NVR, 1024Mbps Record Bandwidth, Supports H.265, H.264 and MJPEG, 16x SATA HDD Bays, Max 192TB, 2x LAN Ports, 1x ESATA, RAID Support, Rack Mountable Chassis, Hard Drives not included	



**Infinique** Infinique, a Canadian company is a manufacturer of high performing end-to-end solutions in copper, fiber and video surveillance systems. For more information visit our website at www.infinique.com or email us at sales@infinique.com.